

6439743

1/19

FIG. 1B




FIG. 1A




FIG. 2B




FIG. 2A








FIG. 3



4/19



5/19




FIG. 7

FIG. 8





FIG. 9



6/19

FIG. 10





FIG. 11




FIG. 12




FIG. 13

7/19




FIG. 14A

FROM  
MODEM




FIG. 14B

8/19




FIG. 15

SENSE BACKSCATTERED LIGHT USING  
THE PLURALITY OF PHOTODIODES

ADJUST DRIVE CURRENTS TO  
LEDs AS A FUNCTION OF  
SENSED BACKSCATTERED LIGHT




FIG. 18B

FIG. 17




FIG. 18A

DETERMINE LED DRIVE CURRENT

DETERMINE LED DIE TEMPERATURE


SELECT CURVE AS A FUNCTION OF  
DETERMINED LED CHARACTERISTICS

DETERMINE TIME LEDs HAVE BEEN ON

DETERMINE TIME TO FAILURE FROM CURVE

FIG. 19


9/19



10/19

FIG. 16B

FROM FIG. 16A



11/19





FIG. 16C



12/19

TO FIG. 16E





FIG. 16D

TO FIG. 16F

13/19



FROM FIG. 16D

14/19





FIG. 16F

15/19




FIG. 16G



FIG. 161



FIG. 16J





FIG. 16K

16/19



17/19

FIG. 20





FIG. 21







FIG. 23




FIG. 24




FIG. 25

